




## General Catalogue

Cat. No.	Description	Substrate	Thick-ness	Length	Peel, g	Tensile kgs	Elonga-tion	Feature and Usage
<b>Dicing Tape</b>								
UP163	UV dicing tape	140μPO	0.17mm	100M	2,200/15	14	600%	Ultra-strong adhesion UV dicing tape for LED modules, etc.
PO803B	PO dicing tape	80μPET	0.09	100M	150	6	400%	Non UV dicing tape, extensionable PO film
<b>Optical film</b>								
C5050	PET protective film	50μPET	0.07	200M	20	18	150%	PET Protective Film for various optical film.
IR50	IR cut film	50μPET	0.065	200M	600	18	150%	IR cut widow film, 90% IR block, 99% UV cut
HC	PET hard coat film	PET	0.188	100M	-	>20	150%	PET hard coat film for panel industry
<b>Functional film for Panel Industry</b> , protective film for mobile, touch panel, etc.								
BS100T	Anti-Scratch PET protective film	100μPET	0.13	200M	6 ~ 8	> 18	100%	Anti-scratch protective film for panels, 3H, silicone adhesive
GS100T	AG protective film	100μPET	0.13	200M	6 ~ 8	> 18	100%	Protective film for panels, silicone adhesive, economic grade
PONA100	Anti-Acid Protective film	80μPET	0.215	200M	20	>20	100%	Protective film for glass during HF and HCl Etching process
DSA50	Low adhesion laminating film	50μPET	0.08	200M	>800/6	>18	150%	Low adhesion silicone laminating film for optical film
BH5023	Hard coat laminating film	50μPET	0.07	200M	>800/3H	> 18	150%	Hard coat laminating film for optical film
GH5023	Anti-Glare (AG) laminating film	50μPET	0.07	200M	>800/3H	> 18	150%	Anti-Glare (AG) laminating film for optical film
DHH50	Optical Clear Double Side film	50μPET	0.09	200M	>1,000	> 18	150%	Optical clear strong adhesion double side film
DSHK50	Black low adhesion laminating film	50μPET	0.08	200M	>800/6	> 18	150%	Low adhesion silicone, black laminating film for panel
<b>Products for Electrical Industry</b>								
PT-25	PET Electrical Tape	25μPET	0.055	50M	600	9.5	100%	For wrapping and fixing of transformers, 130°C, 
PT-13	PET Flame R. Electrical Tape	25μPET	0.055	66M	600	9.5	100%	Flame retardant grade of PT25, CTI 600V, Group I, UL130°C 
PT-155	PEN Electrical Tape	25μPEN	0.055	50M	600	10	80%	For electrical and FPC use UL155°C
PT-683	Cleaning Tape	synthetic PP	0.082	20M	300	18	120%	Cleaning tape for PCB cleaning process
PT-83	Polyimide Tape acrylic adhesive	25μ polyimide	0.075	33M	1,000	13	55%	For electrical and FPC use UL155°C 
PT-85	Polyimide Tape silicone adhesive	25μ polyimide	0.06	33M	800	13	55%	For high temperature electrical and FPC use, 200°C
PT-845	PET Silicone Tape	50μPET	0.08	33M	800	18	120%	High temperature fixing tape for solar cell modules
<b>Double sided tapes / foam tapes</b>								
DHH10	Ultra-thin PET Double Sided Tape	3.5μPET	0.01	200M	200	1	20%	Ultra-thin 3.5μPET double side tape with acrylic adhesive
DP01	PET Double Sided Tape	25μPET	0.085	50M 22M	600	9.5	100%	PET double side tape with acrylic adhesive
PKG121	Double Sided PE Foam Tape	1 mm PE PE liner	0.12	300M	1,500	3	300%	fixing of car trim stripe, and solar cell module frame, etc.
<b>Miscellaneous tapes</b>								
PT-40	OPP Application Tape	40μOPP	0.05	100M	150	9	70%	Application tape for PVC label cutting
PT50LD	PET Hot Fix Tape	50μPET	0.06	100M	350	18	100%	Hot Fix Transfer tape for planar metal parts and fixing tape for clean room
PT90AS	Anti-static PET Tape	23μPET	0.045	50M	600	8	100%	Anti-static packing